



EGA

perfil

ROW CLOSED POST


The best solution for hard and stony grounds in medium-high sized production vineyards

AGRICULTURE
3.0

AVDA. DE LOS CASTAÑOS, Nº 15 · POL. IND.
SAN MIGUEL 31132 · VILLATUERTA (NAVARRA)
T. (+34) 948 32 16 20 F. (+34) 948 32 16 21
egaperfil@egaperfil.com
www.egaperfil.com

ROW CLOSED POST

The best solution for hard and stony grounds in medium-high sized production vineyards



standard lengths (mm): 2200 / 2000 and 1800.
The desired length can be produced on demand.

GENERAL SPECIFICATIONS:

Our posts have mix notches (parallel above and alternate below) for greater versatility and resistance.

If it's required we produce different types of notches: parallel, alternate, central drill, horizontal notches (H), automatic revail (RA) or a combination of some of them.

The posts are marked with the year when they are manufactured.

The posts are totally prepared for integrated mechanization (harvest, cutting, etc.) according to the chosen post.

Depending of the type of terrain and instalation, it's advisable to nail between 1/3 or 1/4 of the total length.

According to the especification of the vineyard, the distance between row posts could go from 4 to 6 meters.

DESCRIPTION

Closed section 46x31 mm row post with accurate resistance for medium-high sized production and big vegetal development vineyards. Specially recomended for hard and stony grounds. Proper elasticity and torsion for heigh not bigger than 2,20 meters.

QUALITY

TYPE OF STEEL AND COVERING: DX51D Steel, Z-275 Galvanized, according to the EN-10346:2015.

Possible to manufactured on demand different covering (Magnelis...) or with other special types of steel as "Corten" or raw steel.

THICKNESS: 1,50 / 1,20 mm.

CROSS SECTION

A (width) mm. 46

B (height) mm. 31

Weigth per linear meter (kg./ml.): e=1,5 mm. / 1,354
e=1,2 mm. / 1,083

Length tolerance (+/- mm): 3,000

Section tolerance (+/- mm): 1,000

Inertias (e=1,50 mm.) I1 (vertical) mm⁴: 78.823
I2 (horizontal) mm⁴: 30.441

DESIGN AND PACKAGING

Type of notch: Notch N and on demand H and RA.

Quantity of notches per length:

Length (mm)	Units
-------------	-------

1800	9
------	---

2000	9
------	---

2200	12
------	----

Units per package: 200 uts.

Units per full truck

Length (mm)	Units	e=1,50 mm.
-------------	-------	------------

1800	10200	
------	-------	--

2000	9200	
------	------	--

2200	8400	
------	------	--