



Standard lengths (mm): 2500 / 2200 / 2000 and 1800. The desired length can be produced on demand.

GENERAL SPECIFICATIONS

The notches along the post allow to adapt the joiners and chains with the greatest convenience and speed.

The posts are marked with the year when they are manufactured.

The posts are totally prepared for integrated mechanization (harvest, cutting, etc.)

Depending of the type of terrain and instalation, it's advisable to nail 1/3 of the total length.

Recomended not to design lines bigger than 100 metres.

DESCRIPTION

Open shaped 57x45 mm end post with a good mechanical resistance and ground fixing characteristics. It is recommended for medium size production vineyards.

QUALITY

TYPE OF STEEL AND COVERING: DX51D Steel, Z-275 Galvanized, according to the EN-10346:2015.

Possible to manufactured on demand different covering (Magnelis...) or with other special types of steel as "Corten" or raw steel.

THICKNESS: 2,00 mm.

CROSS SECTION

A (width) mm	57	
B (height) mm	45	
Weigth per linear meter (kg./ml)		2,010
Length tolerance (+/- mm)		3,000
Section tolerance (+/- mm)		1,000
Inertias:	I1 (vertical) mm ⁴ :	107.751
	I2 (horizontal) mm ⁴ :	46.315

DESIGN AND PACKAGING

Type of notch Extreme notch Quantity of notches per length			
Length (mm)	Units		
1800	9		
2000	12		
2200	12		
2500	15		
Units per package:	200		
Units per full truck			
Length (mm)	Units		
1800	6800		
2000	6200		
2200	5600		
2500	4800		