



EGA *perfil*

TUBE POST

The origin of the range of products

AGRICULTURE
3.0

AVDA. DE LOS CASTAÑOS, Nº 15 • POL. IND.
SAN MIGUEL 31132 • VILLATUERTA (NAVARRA)
T. (+34) 948 32 16 20 F. (+34) 948 32 16 21
egaperfil@egaperfil.com
www.egaperfil.com



DESCRIPTION

This kind of posts are used as end (diam. 40 e:1,50 mm) or intermediate posts (diam. 32 e:1,50 mm). They are a closed section with accurate resistance for medium sized production, big vegetal development vineyards with changing climatology (strog winds in all directions). Specially recommended for hard, stony and wet grounds. Proper elasticity and torsion for heigh not bigger than 2,00 meters.

QUALITY

TYPE OF STEEL AND COVERING: DX51D steel, hot-dip galvanized, according to EN-10346: 2015.

THICKNESS: 1,50 mm.

CROSS SECTION

Diam. (width) mm	40
Diam. (height) mm	32
Weigth per linear meter (kg/ml):	
diam.: 40 mm. e= 1,5 mm.	1,480
diam.: 32 mm. e= 1,5 mm.	1,180
Length tolerance (+/- mm):	3,000
Section tolerance (+/- mm):	1,000
Inertias:	
I1 = I2 (extremo) mm ⁴ :	67.300
I1 = I2 (intermedio) mm ⁴ :	33.500

DESIGN AND PACKAGING

Type of notch: Perforations are made to accommodate a pin.

Quantity of notches per length:

Length (mm)	Units
2000	3
2250	4
Units per package:	100
Units per full truck	
Length (mm)	Units
2000	10500
2250	7400

Standard lengths (mm): 2250 and 2000.
The desired length can be produced on demand.

GENERAL SPECIFICATIONS:

On demand, all kinds of presentations can be made, drilling at the required distances. Likewise, a marking is made to indicate the nail depth.

Depending of the type of terrain and instalation, it's advisable to nail between 1/3 or 1/4 of the total length.

According to the especification of the vineyard, the distance between row posts could go from 4 to 6 meters.